









These glands are liquid tight, easy to assemble and offer good strain relief with wide clamping range. The lamellar construction of glands provide an excellent grip on the cable. These glands offer gas and water tight sealings. Cable glands with reduced clamping range are also available on request.

Technical Details :	
Material	Polyamide 6
Colour	RAL 7001 (Grey) RAL 9005 (Black)
Protection Class	IP 68, 5 bar
Sealing Ring	Neoprene
Temperature Range	-30°C to +80°C Continuous, +150°C Intermittent
Threads available	Pg, Metric, NPT & PF
Approvals	   


Pg Thread

Size	Cat. No. Grey	Cat. No. Black	Thread Diameter (mm)	Thread Length (mm)	 (mm)	Clamping Range (mm)	Standard Pack (pieces)
Pg 7	BS-01	BS-21	13	8	15	3 - 6.5	100
Pg 9	BS-02	BS-22	16	8	19	4 - 8	50
Pg 11	BS-03	BS-23	19	8	22	5 - 10	50
Pg 13.5	BS-04	BS-24	21	9	24	6 - 12	50
Pg 16	BS-05	BS-25	23	10	27	10 - 14	50
Pg 21	BS-06	BS-26	29	11	33	13 - 18	25
Pg 29	BS-07	BS-27	37	11	42	18 - 25	20
Pg 36	BS-08	BS-28	47	13	53	22 - 32	10
Pg 42	BS-09	BS-29	54	13	60	30 - 38	10
Pg 48	BS-10	BS-30	59	14	65	34 - 44	10

Metric Thread

Size	Cat. No. Grey	Cat. No. Black	Thread Diameter (mm)	Thread Length (mm)	 (mm)	Clamping Range (mm)	Standard Pack (pieces)
M 12 x 1.5	BM-0S	BM-2S	12	8	15	3 - 6.5	100
M 16 x 1.5	BM-EN-01	BM-EN-21	16	8	19	4 - 8	50
M 16 x 1.5	BM-01	BM-21	16	10	22	5 - 10	50
M 16 x 1.5	BM-01L	BM-21L	16	15	22	5 - 10	50
M 20 x 1.5/2	BM-02	BM-22	20	10	24	6 - 12	50
M 20 x 1.5/L	BM-02L	BM-22L	20	15	24	6 - 12	50
M 20 x 1.5/3	BM-03	BM-23	20	10	27	10 - 14	50
M 20 x 1.5/4	BM-04	BM-24	20	15	27	10 - 14	50
M 25 x 1.5	BM-EN-03	BM-EN-23	25	8	29	11 - 17	25
M 25 x 1.5/5	BM-05	BM-25	25	10	33	13 - 18	25
M 25 x 1.5/6	BM-06	BM-26	25	15	33	13 - 18	25
M 32 x 1.5	BM-EN-04	BM-EN-24	32	10	36	15 - 21	25
M 32 x 1.5	BM-07	BM-27	32	18	42	18 - 25	25
M 40 x 1.5	BM-EN-05	BM-EN-25	40	10	46	19 - 28	10
M 40 x 1.5	BM-08	BM-28	40	18	53	22 - 32	10
M 50 x 1.5	BM-09	BM-29	50	18	60	30 - 38	10
M 63 x 1.5	BM-10	BM-30	63	18	65	34 - 44	10

NPT Thread

Size	Cat. No. Grey	Cat. No. Black	Thread Diameter (mm)	Thread Length (mm)	 (mm)	Clamping Range (mm)	Standard Pack (pieces)
NPT 3/8"	BSPA-01	BSPA-21	16.70	15	22	5 - 10	50
NPT 1/2"	BSPB-02	BSPB-22	20.95	15	24	6 - 12	50
NPT 1/2"	BSPC-02	BSPC-22	20.95	15	27	10 - 14	50
NPT 3/4"	BSPD-03	BSPD-23	26.40	15	33	13 - 18	25
NPT 1"	BSP-04	BSP-24	33.20	18	42	18 - 25	20
NPT 1 1/4"	BSPE-05	BSPE-25	41.90	15	46	18 - 25	20